

# Houston Hoedown 2023 Diesel Pickup Truck Pulling Rules

## **8500# Work Stock Trucks**

-Weights are allowed but limited to the box of the truck in a secured manner. **No hanging weight out front.**

**-Maximum Hitch Height of 26'' will be measured from center of clevis (if used). Homemade hitch must have a 3 1/2'' diameter opening for sled hook.**

**-No hood stacks.**

-Engine and turbo must be stock appearing. No dual injection pumps, multiple turbo setups, or bored out engines.

-Must run No. 2 diesel, **no nitrous, propane, or water injection.**

-Programmeters allowed. As are larger than stock injectors.

-RPM not to exceed 4500 for safety.

-Traction bars and suspension stops allowed.

- DOT tires only. **NO cut tires, skid steer, or AG tires.**

**No non-stock duals and must have factory front end.**  
(2500/3500 parts. Must be stock rear wheel setup.)

## **8000# Street Mod**

-Hanging weight out front allowed but at the discretion of officials. Must be secured, weights falling off is a disqualification.

**--Maximum Hitch Height of 26'' will be measured from center of clevis (if used). Homemade hitch must have a 3 1/2'' diameter opening for sled hook.**

**-Hood stacks allowed.**

**-Engines can be bored over factory specs, run multiple/larger than stock turbos, and any injection system.**

**-No RPM limit.**

**-Cut tires allowed, as are duals.**

**-Please use common sense and think of others' safety when pulling. Officials will deem a vehicle unsafe if necessary and not allow it to pull.**

**“Street Mod” is a “run what you brung” class meant to have fun.**

Be sure to spread the word to get another truck pull out there to continue this sport.

Any questions or concerns please contact **Joe Hongerholt**

**507-458-0598** (Cell evenings)